


2 Sidemall 'a' exterior elevation

1 | SCALE: |/8" = |-0"



SIDEMALL B' EXTERIOR ELEVATION

1 SCALE: 1/8" = 1'-0"

ADD SGL. KNEE BRACES PER DETAILS A/2 AT THIS ENDWALL TO PEAK TO EAVE T.O. CONCRETE ENDWALL RAFTER CORNER COLUMN

ENDWALL 'A' INTERIOR ELEVATION

SCALE: 1/8' = 1'-0'

FRAME #

ADD SGL. KNEE BRACES PER DETAILS A/2 AT THIS ENDWALL TO PEAK TO EAVE CORNER COLUMN

ENDWALL 'B' INTERIOR ELEVATION

IMPORTANT: IN ADDITION TO THESE PLANS (WHICH ALWAYS TAKE PRECEDENCE), YOU SHOULD HAVE THE FOLLOWING FROM ACT BUILDING SYSTEMS:

- CONSTRUCTION PACKAGE
- INSTALLATION MANUALS - CONSTRUCTION VIDEOS

PLEASE CONTACT YOUR SALES REP IF YOU HAVE NOT RECEIVED THESE PRIOR TO STARTING CONSTRUCTION.

PROJECT DESIGN CRITERIA




SEISMIC DESIGN OF LATERAL FORCE-RESISTING SYSTEMS ARE AS FOLLOWS;

- TRANSVERSE, ORDINARY STEEL MOMENT FRAME (SEISMIC DESIGN IS BASED ON ASCE 07-16, SECTIONS 12.1 - 12.18)

- LONGITUDINAL: ORDINARY STEEL BRACED FRAME, (SEISMIC DESIGN IS PERFORMED USINS THE SIMPLIFIED DESIGN PROCEDURE (ASCE 07-16, SECTION 12.14).

DESIGN BASE SHEAR: IS SHOWN ON CALCULATION SHEET M2.


COMPONENT DIAGRAM




DEFLECTION LIMITS

PURLINS: L/150 (STD) GIRTS: L/90 (STD) L/120 (STD) EM WIND COLUMNS: MALL PANEL L/60 (STD)

ROOF DIAPHRAGM NOTE ROOF SHEETING IS USED AS DIAPHRAGM TO BRACE THE BUILDING AND IS NOT TO BE CUT UNDER ANY CIRCUMSTANCES



ROOF FRAMING PLAN 1 SCALE: 1/8" = 1'-0"



NOTE: USE 1/2" X S' DEMALT 'SCREM-BOLT+' ANCHOR IN 31/2" DEEP HOLES AT ANCHOR LOCATIONS PER BASE DETAIL F/2, INSTALLED PER ICC REPORT ESR-3889,

NOTE: SEE "TYP, FRAME CROSS-SECTION" DETAIL ON SHEET 2 FOR SPECIFIC FRAME DETAIL INFORMATION.

FOUNDATION PLAN SCALE: 1/8" = 1'-0"

DING ® S M CTBUILI SYSTE

 \triangleleft

CONSTRUCTION

Buildings Buildings Avenue NW s, MI 49504 Steel Steel

801 Broadway A Grand Rapids, Toro oro

OB

10/29/2024

VNUJ98563015